



AKCINĖ BENDROVĖ
Stock Company
Savanorių pr.124C, LT-03153 Vilnius
Tel. (+370~5) 213 1850, faksas (+370~5) 213 5570

DECLARATION OF PERFORMANCE

Nr. S-17/4
Nr.

1. Unique identification code of the product-type: ETNA EPS S
2. Intended use:
Expanded polystyrene boards without coating for use in thermal insulation for buildings
3. Manufacturer:
Silikatas, AB, Savanorių pr. 124C, LT-03153 Vilnius, www.silikatas.lt
- 3a. Manufacturing site:
Silikatas, AB, Statybininkų g. 1M, LT-21389 Vievis, phone (+370 528) 38 207
4. Verification of constancy:
System 3
5. Declared performance:

Essential requirement	Performance	Harmonised technical specification
Thickness of insulation	See the label of the product	LST EN 13163
Declared heat conductivity	0.043 W/(m*K)	LST EN 12667
Thermal resistance	See the label of the product	LST EN 13163
Compressive strength, CS(10)	≥ 40kPa	LST EN ISO 29469
Bending strength, BS	≥ 50kPa	LST EN 12089
Dimensional stability, DS(70,90)I	-	LST EN 1604
Reaction to fire	E	LST EN 13501-1
Long term water absorption after total immersion, WL(T)	-	LST EN ISO 16535
Dimensional change		LST EN 13163
Length, L(3)	±3mm	LST EN ISO 29465
Width, W(2)	±2 mm	LST EN ISO 29465
Thickness, T(2)	±2 mm	LST EN ISO 29466
Straightness, S(5)	±5mm/1000mm	LST EN 824
Flatness, P(5)	±5mm	LST EN ISO 29468

Durability — ETNA is resistant to rotting, decaying, volumetric changes, its thermal insulation and mechanical properties are maintained throughout the use of the building.

6. The performance of the product specified corresponds to all declared performance. This declaration of performance is drawn in accordance with the Regulation (EU) No. 305/2011, responsible for creating this declaration of performance is only the manufacturer referred to in the declaration.

Signed on behalf of the manufacturer and in the name of the manufacturer by:

Vytautas Česnauskas, Managing Director

(name and function)

Vilnius, 2026-10-20

(issue place and date)

(signature)

CE